

Molded connector, form A, analogue with EN 175301-803 (ISO 4400)

Molded sheathing

Color	anthracite (translucent)
Material	TPU
Imprint	circuit diagram; white; on front side

Terminal block

Material	PA6 GF15
Poles	2 + 2 PE
Direction of protecting earth	6/12 h
Contact distance	18 mm

Cable

Jacket	PVC, black
Internal cores	yellow/green, blue, brown
Cores x cross-section	3 x 0,75 mm ²
Outer diameter	ca. 6,7 mm
Length (L)	3,00 m
Stripping (A)	30,0 mm
Core ends	equipped with wire end sleeves
Temperature range (fix)	-30 ... +80°C
Temperature range (flexible)	-5 ... +70°C

Contacts

Material	CuZn, coated with Cu/Sn
Forward resistances	< 15 mOhm

Gasket

Type	TPU, molded
------	-------------

Fastening screw

Material	A2-50 (stainless steel)
Size	M3 x 26,0 mm
Recess type	cross recess (type H) with longitudinal slot
Tightening torque	0,4 ± 0,1 Nm

Circuit

Built-in electronics	LED + varistor
LED	red
Protecting element	yes, varistor
Voltage range	24 V ± 15 %
Current type	AC/DC
Operating current	max. 1,50 A (Derating is to be considered.)
Protection against wrong polarity	yes

General properties


Temperature range *	-25 ... +90°C
RoHS	yes
Protection grade (IEC 60529) **	IP67

Packaging



60 pcs packaging.
2x30 pcs. fastening screw in plastic bags.
Size of the cardboard box: 380x260x260 mm.
packaging weight: ca. 14,1 kg

* Depends on the connected cable.

** Must be tested in properly mounted state on the counterpart.



Imprint



				Zulässige Abweichung für Maße ohne Toleranzangabe Unless otherwise specified tolerances DIN ISO 2768-v	Format/Size: A4		Maßstab/Scale:		Gewicht/Weight: 235 g/pcs							
6	31323	21.03.2022	TTO		Schutzvermerk ISO 16016 beachten Observe protection note ISO 16016	Werkstoff: Material:		Benennung: Title: Molded con A2+2E12 PVC3x0,75 3,00m 03Br								
5	30748	12.01.2022	BAL													
4	28333	01.03.2018	GJO													
3	26609	08.02.2016	PKR													
2	26600	01.02.2016	PKR													
1	26443	27.10.2015	PKR													
Ind Rev	Änderung-Nr. Change no.		Datum Date	Name By												
Geprüft: Checked:		21.03.2022 JONAS														
Erstellt: Created:		27.02.2014 KROZSER														
					Ident. - Nr.:		611-202-0273		Freigabe-Nr.: Approval no.:		25306		Blatt: Sheet:		1/1	
					Ersatz für/Replacement for:											