

Molded connector, form A, analogue with EN 175301-803 (ISO 4400)

Molded sheathing

Color	anthracite (translucent)
Material	TPU
Imprint	circuit diagram; white; on front side

Terminal block

Material	PA6 GF15
Poles	2 + 2 PE
Direction of protecting earth	6/12 h
Contact distance	18 mm

Cable

Jacket	PVC, black
Internal cores	yellow/green, blue, brown
Cores x cross-section	3 x 0,75 mm ²
Outer diameter	ca. 6,7 mm
Length (L)	5,00 m
Stripping (A)	30,0 mm
Core ends	equipped with wire end sleeves
Temperature range (fix)	-30 ... +80°C
Temperature range (flexible)	-5 ... +70°C

Contacts

Material	CuZn, coated with Cu/Sn
Forward resistances	< 15 mOhm

Gasket

Type	TPU, molded
------	-------------

Fastening screw

Material	A2-50 (stainless steel)
Size	M3 x 26,0 mm
Recess type	cross recess (type H) with longitudinal slot
Tightening torque	0,4 ± 0,1 Nm

Circuit

Built-in electronics	LED + bridge rectifier + varistor
LED	red
Protecting element	yes, varistor at input, diodes at output
Voltage range	12 V - 48 V
Current type	AC/DC
Operating current	max. 1,50 A (Derating is to be considered.)
Protection against wrong polarity	yes

General properties


Temperature range *	-25 ... +90°C
RoHS	yes
Protection grade (IEC 60529) **	IP67

Packaging



30 pcs packaging.
1x30 pcs. fastening screw in plastic bags.
Size of the cardboard box: 380x260x260 mm.
packaging weight: ca. 11,1 kg

* Depends on the connected cable.

** Must be tested in properly mounted state on the counterpart.



Imprint



				Zulässige Abweichung für Maße ohne Toleranzangabe Unless otherwise specified tolerances DIN ISO 2768-v	Format/Size: A4	Maßstab/Scale:	Gewicht/Weight: 370 g/pcs	
					Schutzvermerk ISO 16016 beachten Observe protection note ISO 16016	Werkstoff: Material:		
						Benennung: Title: Molded con A2+2E12 PVC3x0,75 5,00m 09Ir		
2	31323	21.03.2022	TTO					
1	30748	12.01.2022	BAL					
Ind Rev	Änderung-Nr. Change no.	Datum Date	Name By					
Geprüft: 21.03.2022 Checked: JONAS								
Erstellt: 12.11.2015 Created: KROZSER					Ident. - Nr.: 611-202-0388		Freigabe-Nr.: 26443 Approval no.:	Blatt: 1/1 Sheet:
					Ersatz für/Replacement for:			