

Connector, form B, industrial type

Housing


Type	one-piece
Color	opaque (milky)
Material	PA6 GF20
Imprint	circuit diagram; black; top side

Cable gland

Thread	M16 x 1,5 mm
Cable diameter	6-8 mm
Color	black
Material	PA6 GF30
Tightening torque	1,8 ± 0,2 Nm

Terminal block


Material	PA6 GF30
Poles	2 + PE
Direction of protecting earth	12 h
Contact distance	11 mm



④ Contacts **

Material	CuZn, tin-plated
Resistance	< 15 mOhm
Conductor cross-section	0,5 - 1,5 mm²
Tightening torque	max. 0,3 Nm

Logo




Gasket

Material	NBR, black
Type	flat

Fastening screw

④ Material	steel 4.8, coated with zinc-nickel
④ Size	M3 x 34,0 mm (with cross recess)
Tightening torque	0,4 ± 0,1 Nm
Sealing washer	n/a

Circuit diagram



Circuit

Circuit	function display LED
Color of LED	green
Protecting element	n/a
Voltage	24 V ± 15 %
Current type	AC / DC
Operating current	max. 10 A
Protecting against wrong polarity	yes

General properties

Ambient temperature range	-25°C ... +90°C
RoHS	yes
CSA approval	n/a
Protection grade (IEC 60529) *	IP65

Packaging

100 pcs packaging. Terminal block and housing are packed in pre-assembled condition. Cable gland componets are pre-assembled in housing. Fastening screw is inserted in the packet in packaged condition. Flat gasket is inserted into the packet in packaged condition.

* Must be tested in properly mounted state on the counterpart.

** In order to establish a suitable electrical connection, the use of ferrules for stranded respectively fine-stranded conductors is mandatory. Be aware that the conductor cross-section affects the maximum current-load capacity.

				Zulässige Abweichung für Maße ohne Toleranzangabe Unless otherwise specified tolerances		Format/Size: A4		Maßstab/Scale:		Gewicht/Weight:							
				DIN ISO 2768-v		Werkstoff: Material:											
4				31645		07.10.2022		BKI		Schutzvermerk beachten Observe protection note ISO 16016		Benennung: Title: Connector field att. I 01Bg					
3				31531		13.07.2022		BKI									
2				29839		14.02.2020		AKO									
1				29397		26.06.2019		GJO									
Ind Rev		Änderung-Nr. Change no.		Datum Date		Name By				Ident. - Nr.: 612-201-0130 Freigabe-Nr.: Approval no.: 27722 Blatt: Sheet: 1							
Geprüft: Checked:		07.10.2022 JONAS															
Erstellt: Created:		02.05.2017 MANGRA															
Ersatz für/Replacement for:																	