


M8 round connector acc. to IEC 61076-2-104:2008

Projected view



General specifications

Form	M8
Connection	male
Connection type	angled
Number of pins	3

Mechanical specifications

Contact elements	spring-loaded contact socket
Pin diameter	1 mm
Contact materials	CuSn / Au
Contact surface	Au
Body	TPU, black
Sleeve connector	Diecast zinc

Cable

Sheath material	PVC
Sheath color	grey
Sheath diameter	Ø 4,8 mm
Lenght	3 m ± 50mm
Core isolation	PVC
Number of cores	3-core
Conductor construction	19 x Ø 0,15mm
Cross-section	3x0,34 mm²

Elektrical specifications

Operating voltage	max. 60V DC
Operating current	max. 4A

General properties

Ambient temperature	-5 ... +70°C
IP protection degree acc. to EN 60529:2000	IP67/IP68/IP69K


Packaging

Single package

Color of cores

1-brown
3-blue
4-black

Positions of contacts



					Zulässige Abweichung für Maße ohne Toleranzangabe Unless otherwise specified tolerances	Format/Size: A4	Maßstab/Scale:	Gewicht/Weight:		
					DIN ISO 2768-v	Werkstoff: Material:				
					Schutzvermerk beachten Observe protection note ISO 16016	Benennung: Title: Round connector M8 male angled 5/3 PVC 3,00m				
Ind Rev	Änderung-Nr. Change no.	Datum Date	Name By		Ident. - Nr.:	617-202-0106	Freigabe-Nr.: Approval no.:	26886	Blatt: Sheet:	1/1
Geprüft: Checked:		01.08.2016 PAL			Ersatz für/Replacement for:					
Erstellt: Created:		01.08.2016 MANGRA								