

M12 round connector acc. to IEC 61076-2-104:2008

General specifications

Form	M12
Connection	female
Connection type	angled
Number of pins	4

Mechanical specifications

Contact elements	spring-loaded contact socket
Pin diameter	1 mm
Contact materials	CuSn / Au
Contact surface	Au
Body	TPU, black
Sleeve connector	Diecast zinc

Cable

Sheath material	PVC
Sheath color	grey
Sheath diameter	Ø 4,3 mm
Length	3 m ± 50mm
Core isolation	PVC
Number of cores	4-core
Conductor construction	19 x Ø 0,15mm
Cross-section	4x0,34 mm ²

Elektrical specifications

Operating voltage	max. 60V DC
Operating current	max. 4A

General properties

Ambient temperature	-5 ... +70°C
IP protection degree acc. to EN 60529:2000	IP67/IP68/IP69K


Packaging

Single package


Color of cores

1-brown
2-white
3-blue
4-black

Projected view



Positions of contacts



				Zulässige Abweichung für Maße ohne Toleranzangabe Unless otherwise specified tolerances DIN ISO 2768-v	Format/Size: A4	Maßstab/Scale:	Gewicht/Weight:	
					Schutzvermerk beachten Observe protection note ISO 16016	Werkstoff: Material:		
						Benennung: Title: Round connector M12 female angled 5/4 PVC 3,00m		
Ind Rev	Änderung-Nr. Change no.	Datum Date	Name By					
Geprüft: Checked:		01.08.2016 PAL			Ident. - Nr.: 617-202-0172	Freigabe-Nr.: Approval no.: 26886	Blatt: Sheet: 1/1	
Erstellt: Created:		01.08.2016 MANGRA						
					Ersatz für/Replacement for:			