

Connector, form A, analogue with EN 175301-803 (ISO 4400)

Housing

Type	two-piece
Color	black, with milky cover
Material	PA6 GF30 / PA6 GF20
Imprint	circuit diagram; black; top side

Cable gland

Thread	M20 x 1,5 mm
Cable diameter	6-8 mm
Color	black
Material	PA6 GF30
Tightening torque	1,8 ± 0,2 Nm

Terminal block

Material	PA6 GF30
Poles	2 + PE
Direction of protecting earth	12 h
Contact distance	18 mm

Contacts

Material	CuZn, tin-plated
Resistance	< 15 mOhm
Conductor cross-section	0,5 - 1,5 mm ²
Tightening torque	0,2 ± 0,1 Nm without protection element

Gasket

Material	NBR, black
Type	profile

Fastening screw

③ Material	steel 4.8, coated with zinc-nickel
③ Size	M3 x 37,0 mm (with cross recess)
Tightening torque	0,4 ± 0,1 Nm
Sealing washer	n/a

Circuit

Circuit	signal amplifier (P-channel FET)
Color of LED	green
Protecting element	yes, diode
Voltage	24 V ± 15 %
Current type	DC
Operating current	max. 1,5 A
Protecting against wrong polarity	no


General properties

Ambient temperature range	-25°C ... +90°C
RoHS	yes
CSA approval	n/a
Protection grade (IEC 60529) *	IP65


Packaging

100 pcs packaging. Terminal block and housing are packed in pre-assembled condition. Cable gland componets are pre-assembled in housing. Fastening screw is inserted in the packet in packaged condition. Profile gasket is inserted into the packet in packaged condition.


* Must be tested in properly mounted state on the counterpart.



Logo



Circuit diagram



				Zulässige Abweichung für Maße ohne Toleranzangabe Unless otherwise specified tolerances DIN ISO 2768-v	Format/Size: A4	Maßstab/Scale:	Gewicht/Weight:
					Werkstoff: Material:		
					Benennung: Title: Connector field att. A 29Bg		
3	31664	19.10.2022	BKI	Schutzvermerk beachten Observe protection note ISO 16016			
2	29838	19.02.2020	AKO				
1	29379	19.06.2019	GJO				
Ind Rev	Änderung-Nr. Change no.	Datum Date	Name By		Ident. - Nr.:	Freigabe-Nr.: Approval no.:	Blatt: Sheet:
Geprüft: Checked:		19.10.2022 JONAS			611-201-0296	26370	1
Erstellt: Created:		11.09.2015 KROZSER			Ersatz für/Replacement for:		